

Артикул 9043 1.4006 TX ШУРУПЫ ДЛЯ СТРОИТЕЛЬСТВА ТЕРРАС T-DRILL С ПОЛУПОТАЙНОЙ ГОЛОВКОЙ И РЕЖУЩЕЙ КАНАВКОЙ

ITEM 9043 1.4006 TX
T-DRILL, RSD CSK HEAD TERRACE SCREWS, CUTTING POINT



ПРИМЕНЕНИЕ:

Идеально подходят для деревообрабатывающих предприятий (столярных мастерских, строителей деревянных сооружений) и любых садовых и ландшафтных работ для крепления террасных досок и причалов. Отлично подходят даже для древесины твердых пород, например бангирай, массарандуба и т. д.

Должна обеспечиваться минимальная глубина вкручивания (от 4 диаметров). В зависимости от породы древесины может потребоваться глубина вкручивания, равная 8 диаметрам.

USES:

Ideal for all companies involved in wood processing (carpenters, timber construction) and all horticulturists and landscapers for fastening timbers and landing stages. Also the ideal solution for hardwoods such as Bankirai, Massaranduba, and many more.

A minimum screw-in depth of 4 x the diameter must be ensured. A screw-in depth of 8 x the diameter should be achieved depending on the wood.

ХАРАКТЕРИСТИКИ:

- Усиленная головка.
- Режущие ребра.
- Стабилизированное тело.
- Оригинальное расположение боковой стороны профиля резьбы.
- Режущая канавка.
- Фрезерирующие ребра под головкой.
- Звездобразное углубление под ключ TX.
- Высококачественная мартенситная сталь (1.4006).
- Специальное скользящее покрытие.

FEATURES:

- Reinforced head
- stripping ribs
- Stabilised shaft
- New kind of threaded flank arrangement
- cutting point
- ribs under the head
- TX driving feature
- Martensitic stainless steel hardened (1.4006)
- Special smooth coating

Высококачественная
мартенситная сталь класса
С1
1.4006

d d	l l	b b	dk dk	k k	Привод Drive size	Арт. № Item Number	
5	40	26	7,95	3	TX25	9043400650 40	200
	50	36	7,95	3	TX25	9043400650 50	200
	60	40	7,95	3	TX25	9043400650 60	200
	70	50	7,95	3	TX25	9043400650 70	100
	80	50	7,95	3	TX25	9043400650 80	100

